

Model No.

SNF 20

Salient Features

- Gen X Safe Cranes
- CEV BSV Engine
- Fire Extinguisher
- Human Proximity Sensor
- Low Maintenance Cost
- Cabin Front Glass Guard
- Heavy Duty Structure
- Helper Seat
- Air Brakes
- Spacious Driver Cabin
- Digital Cluster
- Music System
FM/AM/Bluetooth/USB
- Mobile Charger Port

Optional Features

- Fly Jib
- SLI
- Over Hoist cutoff
- Man Basket
- Six Fall
- Rear View Camera
- 360° View Camera
- Dragwinch
- Telematic (GPS)
- AC Cabin



COLOR OPTIONS

		
Red/White (STD)	Yellow/White	Green/White

San Systems & Controls Pvt. Ltd.

Corporate Office: Plot No. 34, Sector-58, HSIIDC Industrial Estate, Faridabad- 121004

Manufacturing Plant: Khata No. 144/154, Kila No. 26, Mohala Schralla Road, Village Schralla, Distt. Palwal - 121102, Haryana

Email: sales@sangroupindia.in Website: www.sangroupindia.in

Phone No.: +91 9810088634, 9817549646



SPECIFICATIONS SNF 20 - 20 Tonnes

LIFTING CAPACITY

20 Tonnes @ 1.5 m Radius

Boom Height

65 Feet

ENGINE

TATA 497 BS V CEV 101PS@2200rpm

TRANSMISSION

Heavy duty, Syncro mesh with 6 forward and 1 reverse speeds with high low range selector.

Heavy duty, single, dry friction, cerametallic clutch plate with diaphragm type pressure plate.

BRAKES

Pneumatic Front and rear brakes are actuated through a single pedal. Parking brake is provided

POWER STEERING

40° articulation through 2 hydraulic cylinders on either side

HYDRAULIC SYSTEM

- Gear/Inba vane type pump
- Five/Six spools control valve.
- Suction line has 100 mesh size strainer while return line is fitted with 25 micron filter.
- Two double acting IR cylinders five double acting steering cylinders and one double acting extension cylinder.

HOIST

Winch is driven by hydraulic motor employing 4 falls of 13 mm dia rope and fitted with hook block. 50 Mtr /Min. (Line speed)

TELESCOPIC BOOM

4 parts boom, 2 parts hydraulically powered & fully synchronized, 4th part manual power assisted.

VEHICLE PERFORMANCE

Speed Max.	34 km/h
Creep Speed	1.2 km/h
Graduability	40% unieden

DRIVE

4WD

ELECTRICAL SYSTEM

12V. Negative earth

Luff Range

-5" to +68"

TYRES

Front : 12.00 x 24 - 20 PR (4 Nos.)

Reor : 12.00 x 24 - 20 PR (4 Nos.)

SAFETY

- Audio overhoist indication.
- Hose failure protection.
- Audio over hoisting indication.
- Safety brakes on hoist.

STANDARD EQUIPMENT

- Cabin
- Front tyre protector
- Front and rear work lights
- Reflectors & rear view mirror
- Tool kit
- Fire Extinguisher

OPTIONAL EQUIPMENT

- Fiyj-b. (1.25 tonnes max capacity)
- AC Cabin
- Over hoisting hydraulic cut off
- Sale load indietor/ LMI
- Drag winch
- Man basket
- Six tail
- Telematics
- Reor View Camera
- 360° View Camera

CAPACITIES

FUEL TANK	200 LTR
-----------	---------

HYDRAULIC TANK 200 LTR

OVERALL WEIGHT


FRONT 8400

REAR	10130
------	-------

TOTAL	18530
-------	-------



LOAD CHART SNF 20

[illegible]